

Spec/Model	ELF-10	ELF-12	ELF-15	ML-10	ML-12	SPLW-10	SPLW-12	SPLW-15
Power	500	500	700	1200	1200	2200	2200	2900
Mag. Wgt. (oz)	55	60	80	160	160	270	340	340
V.C. Size (in.)	1.5	1.5	2.0	2.0	2.5	3.0	4.0	4.0
V.C. Imp	4Ωx2	4Ωx2	4Ωx2	4Ωx2	4Ωx2	1Ωx2	1Ωx2	1Ωx2
Fs (Hz)	31.9	29.05	23.03	36.74	33.52	30.4	30.58	29.0
Vas (Cu. Ft.)	1.96	3.61	6.88	1	1.53	0.6	0.925	1.6
Qms	4.014	4.407	7.05	2.94	3.41	4.19	4.86	4.37
Qes	0.485	0.543	0.4653	0.702	0.469	0.266	0.365	0.352
Qts	0.4323	0.4836	0.7365	0.5668	0.412	0.2503	0.3394	0.326
Xmax (in.)	0.2	0.2	0.2	0.26	0.315	0.394	0.473	0.59
SPL	91	92	93	91	92	89	90	92
Box Style	S/P	S/P	S/P	S/P	S/P	P	P	P
Box Size (S) (Cu.Ft.)	0.5	1.5	2.5	0.5	0.75	N/A	N/A	N/A
Box Size (P) (Cu. Ft.)	1.6	2.1	4.25	1.4	1.7	1.65	2.4	3.4
Port Size (dia."xL")	3x7.75	3x8.3	3x3.2	3x11.5	3x10	3x9.25	4x16.75	4x10
# of Ports	1	1	1	1	1	2	2	2
Tune Freq. (Hz)	35	30	29	33	32	45	40	40
Hole Dia. (in.)	9.13	11	14.0	9.5	11.13	9.25	11.5	14.0
Depth (in.)	4.6	5.5	6.2	5.875	6.5	6.375	7.25	8.875
Outer Ring (in.)		12.25		10.5	12.38	10.25	12.75	15.25

Box Styles:

S = Sealed

P = Ported

F = Free Air